



E232

Desktop Installation

RS-232 Serial Port to E1 Converter

- Support 1 RS-232 serial port and 1 E1 port
- Support signal indication of E1 port data, E1 port loss of synchronism and upstream alarm
- Support optional clock: internal clock, external clock, recovery receiving clock
- Support E1 port loopback and RS-232 loopback
- Two optional power supplies: 220VAC or -48VDC
- Support -25 ~ 70°C wide operating temperature range



Introduction


E232 is a RS-232 to E1 converter which could implement bidirectional conversion between RS-232 serial port and E1 digital port. It adopts desktop mounting to meet the requirements of different scenes.

The data port of this device is operating at a rate of unframed 2.048Mbps of E1. User data has accounted for all 32 timeslots of E1 frame. The main E1 link could provide 3 types of clock source: E1 port recovery clock, internal clock and external clock of digital port. E232 provides loopback and phase adjustment function, which is convenient for digital port testing.

DIP switch could implement functions like impedance setting, BNC grounding setting, clock setting, loopback setting, restoring to factory setting, etc. Hardware adopts fanless, low power consumption, wide temperature range design, and can be widely used in various departments and systems such as industrial control, environment monitoring, network monitoring, etc.

Dimension

Unit: mm



Specification

E1 Port	Interface Protocol Standard: conform to the recommendation of ITU-TG.703 Output Jitter Transfer: conform to the recommendation of
---------	--

	<p>ITU-TG.735</p> <p>Input Jitter Tolerance: conform to the recommendation of ITU-TG.823</p> <p>Output Jitter: conform to the recommendation of ITU-TG.823</p> <p>Line Rate: bidirectional 2.048Mbps synchronized data</p> <p>Transmission Distance: 2km</p> <p>Clock Recovery Accuracy: ±50ppm</p> <p>Interface Code Pattern: HDB3</p> <p>Frame Format: un-framing</p> <p>CRC Check: No</p> <p>Clock Frequency: 2.048MHz</p> <p>Interface Connection: BNC, RJ45</p> <p>Interface Impedance: 75Ω imbalance(BNC) and 120Ω balance (RJ45,)</p> <p>Interface Protection: 1500V Electromagnetic isolation</p>
RS-232 Port	<p>Standard: EIA RS-232C</p> <p>Pin Definition: TXD、RXD、CTS、DSR、GND、DCD</p> <p>Interface Rate: 0 ~ 115200bps</p> <p>Transmission Distance: less than 15m</p> <p>Line Code: NRZ</p> <p>Interface Type: DB25 Female (equipped with DB25 male to DB9 female cord)</p> <p>Connection Cable: DB25 male to DB9 female cord</p> <p>Interface Protection: 600W surge protection, 15KV electrostatic protection</p>
Indicator	<p>Power indicator, loss-sync alarm indicator, upstream E1 link whole code1 alarm indicator, E1 link inference alarm indicator, data receiving from G.703 network indicator, data sending to G.703 network indicator</p>
Power Supply	<p>220VAC or -48VDC</p>
Power Consumption	<p>2.00W</p>
Environmental Limit	<p>Operating temperature:-25~70℃</p> <p>Storage temperature: -40~85℃</p> <p>Relative humidity: 5% ~ 95% (no condensation)</p>
Physical Characteristic	<p>Shell: Plastic</p> <p>Installation: desktop installation</p> <p>Dimension (W x H x D): 227.4mm×146.3mm×42.7mm</p> <p>Weight: 260g</p>

Certification

CE, FCC, RoHS

Warranty

3 years

Typical application



Ordering Information

Models	RS-232	E1	Power Supply
E232	1	1	220VAC or -48VDC



Address: 3/B, Zone 1, Baiwangxin High Technology Industrial Park, Song Bai Road, Nanshan District, Shenzhen, 518108, China

TEL.: +86-755-26702668 ext 835 FAX: +86-755-26703485

E-mail: ics@3onedata.com

Website: www.3onedata.com

◀ Please scan our QR code for more details

*Product pictures and technical data in this datasheet are only for reference. Updates are subject to change without prior notice. The final interpretation right is reserved by 3onedata.